



ZEOS-C Fire Alarm Detectors



EN54-5 or/and EN54-7
CERTIFIED

The ZEOS-C series of Fire Alarm Detectors has been designed to be exclusively compatible with the Global Fire Equipment range of conventional detection zones available in the following equipment:

- Conventional Panels: ORION, ORION MINI, ORION EX and ORION-PLUS.
- Addressable Zone Monitoring Units: QUAD-ZMU and ZMU.

Certified to EN54-5 and EN54-7 the ZEOS-C series detectors are available in heat, smoke and combined smoke/heat detector versions.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	10-30 V DC
CURRENT - QUIESCENT	Heat: 7 uA / Smoke: 33 uA / Smoke & Heat: 35 uA
CURRENT - DEVICE IN ALARM	24 mA - Alarm LEDs
SENSITIVITY	According to EN54-5 or/and EN54-7
CABLE SIZE	0.5-2.5 mm ²
RESET/START-UP TIMES	20 seconds max.
COLOUR / CASE MATERIAL	White / ABS
MAX. HUMIDITY	95% RH Non-Condensing
NORMAL / TRANSIENT OPER. TEMPERATURE	0°C to 50°C / -10°C to 85°C
DIMENSIONS	100 mm (D) x 50 mm (H)
WEIGHT	144 g inc. base
COMPATIBILITY	ORION, ORION MINI, ORION EX, ORION-PLUS, QUAD ZMU and ZMU

ORDER CODE

ZEOS-C	1328-CPR-0705	PHOTOELECTRIC SMOKE DETECTOR
ZEOS-C-H	1328-CPR-0706	RATE OF RISE/FIXED TEMP HEAT DETECTOR
ZEOS-C-SH	1328-CPR-0704	MULTISENSOR SMOKE & HEAT DETECTOR