



GFE-MCPE-C

Conventional Manual Call Point



The GFE-MCPE-C is a Conventional Manual Call Point, designed and manufactured to comply with EN54-11, compatible with all GFE Conventional Control panels. A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The unit is supplied complete with a hinged flap which protects the trigger element from accidental activation and reduces malicious activations as two actions are required in order to activate the device. This unit can be both surface and flush mounted and it can be easily reset using the supplied key after activation.

TECHNICAL SPECIFICATIONS

OPERATION VOLTAGE	20-30 V DC
CURRENT CONSUMPTION - QUIESCENT	200 uA
CURRENT CONSUMPTION - ALARM	50 mA @ 24 V DC nominal - Alarm Resistance 470 Ohms max.
OPERATING TEMPERATURE	-10°C to 55°C
STORAGE TEMPERATURE	-30°C to +60°C
INGRESS PROTECTION GRADE	IP24D - Type A - Indoor Use
MAX. HUMIDITY	95% RH Non-Condensing @ 40°C
COLOUR / CASE MATERIAL	Red / ABS & Clear/ PC - Flame Retardant - Rating 94V0
DIMENSIONS - SURFACE MOUNTED	92.6 (W) x 92.6 (H) x 60.1 mm
DIMENSIONS - FLUSH MOUNTED	92.6 (W) x 92.6 (H) x 27.8 mm
WEIGHT	152 g includes back box and fixings

ORDER CODE

GFE-MCPE-C	1328-CPR-0377	CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-BLUE	1328-CPR-0377	BLUE CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-GREEN	1328-CPR-0377	GREEN CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-YELLOW	1328-CPR-0377	YELLOW CONVENTIONAL MANUAL CALL POINT
GFE-MCPE-C-WHITE	1328-CPR-0377	WHITE CONVENTIONAL MANUAL CALL POINT