



GFE-MCPE-C-IP67

Conventional Manual Call Point
Outdoor Use - IP67



The GFE-MCPE-C-IP67 is a Conventional Manual Call Point, designed and manufactured to comply with EN54-11, compatible with all GFE Conventional Control panels specially recommended for outdoor use.

The unit is supplied complete with a hinged flap which protects the trigger element from accidental activation and reduces malicious activations as 2 actions are required in order to activate the device.

A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The GFE-MCPE-C-IP67 has been designed to deal with today's difficult and harsh environments. It is a unique fire alarm manual call point that mimics the feel of breaking glass whilst offering the user the benefits and safety advantages of a glass-free resettable operating element. Once activated a warning flag drops in to view easily identifying the call point that has been operated. A key can then reset the unit.

The GFE-MCPE-C-IP67 provides an ideal solution for most conventional fire alarm systems. Ideal for all outside applications such as oil rigs, ships, factories as well as wash down areas that are sensitive to broken glass.

TECHNICAL SPECIFICATIONS	
OPERATION VOLTAGE	20-30 V DC
CURRENT - QUIESCENT	200 uA
ALARM	50 mA @ 24V DC nominal - Alarm Resistance 470 Ohms max.
OPERATING TEMPERATURE	-10°C to +55°C
STORAGE TEMPERATURE	-30°C to +60°C
COLOUR / CASE MATERIAL	Red and others / ABS & Clear/ PC - Flame Retardant 94 V0
PROTECTION	IP67 - Type A - Outdoor Use
MAX. HUMIDITY	95% RH Non-Condensing @ 40°C
DIMENSIONS	111.9 (H) x 111.9 (W) x 81.3 (D) mm
WEIGHT	262 g includes back box and fixings

ORDER CODE		
GFE-MCPE-C-IP67	1328-CPR-0373	CONVENTIONAL MANUAL CALL POINT, IP67 - OUTDOOR USE